



HOFFENHEIM RHEIN NECKAR ARENA, DE

Product Specifications

Structure

- Horizontal beam structure of 60mm X 40mm X 3mm thk.
- Hollow section pedestal with base plate 6mm thickness for riser mounted.
- BS 3692 Specification for ISO metric precision hexagon bolts, screws and nuts. Metric Units.

Backrest and Seat

- Blow moulded co-polymer.
- UV Inhibitors are added at a rate to ensure no significant colour or plastic deterioration.
- Beam mounted tip-up seat with ergonomically design back and seat.

Metal Finishing

- All metal parts exposed shall be stripped and cleaned with iron phosphate, hot water rinsed and then chromic acid rinsed.
- All metal parts are coated with an epoxy finish of at least 60 microns for indoor use and hot dipped galvanized to BS 729 for outdoor use.
- Conformity with BS-6496 hardness test.

Plastic

- Refer to Ferco plastic color chart.

Advantages

- Comfort especially studied according to fundamental criteria of ergonomic.
- Durability of the chair & after sales service for all spare parts of the model.
- Slim profile creating enhance seat way.
- Curved backrest design for maximum comfort.
- "Steel Beam Clamp" concept giving the ease of relocation of seats along the beam.
- Flexibility of seats by using the steel beam clamp for easy installation & maintenance.

Fire Resistance


- Flammability compliance with California Bulletin 117 and international regulations. in their last issues and particularly with safety regulations.

Warranty

- Refer to Ferco product warranty.


Options

- ARC multi with P.U
- ARC multi plus
- ARC multi with cupholder
- ARC multi with retractable armrest
- ARC Wrimatic
- ARC Left hand armrest
- ARC end cap with row lettering
- ARC end cap with numbering
- ARC aluminium rectangular seat numbering
- Riser mounted leg
- Ultra Violet and Fire Retardant



490 (19.5") Min.

H



C

DIMENSIONS	
H	C
790 (31")	225 (9")