





INTI INTERNATIONAL COLLEGE SUBANG, MALAYSIA



485 (19") 510 (20")
535 (23") 560 (22")



C

DIMENSIONS	
H	C
870 (34")	265 (10.5")

Product Specifications

Backrest

- Inner panel shall be made of 7plys @ 13 mm thick plywood covered with high resilience foam, density 45 kg/m³. Upholstered with padded cover.

Seat

- Fully upholstered seat with padded cover.
- Inner structure made of Ø21mm x Thk. 2.6mm tubular steel frame, integrated with grid foundation in HR foams with a density of 60 kg/m³.
- Tip- up seat with counterweight systems and being lift-up by means of gravity. Totally silent and maintenance free.

Fixed table

- 18mm thickness wooden table and wooden front panel with maica laminated and PVC black edging.

Standards

- Centre and end standards are of lateral pedestal design made of 38mm x 38mm x Thk 2.3mm square hollow section continuous welded to a 6mm thickness steel plate.

Metal Finishing

- All metal parts exposed shall be stripped and cleaned with iron phosphate, hot water rinsed and then chromic acid rinsed.
- All metal parts are coated with an epoxy finish of at least 60 microns for indoor use.

Upholstery Material

- Refer to Ferco standard fabric / leatherette / leather charts.

Advantages

- Comfort especially studied according to fundamental criteria of ergonomic.
- Durability of the chair & after sales service for all spare parts of the model.
- Large choice of fabrics.

Fire Safety

- Fire Safety - Flammability compliance with California Bulletin 117 and international regulations in their last issues and particularly with safety regulations.
- Flammability compliance with BS 5852 : 2006 Section 3 Ignition Source 0 & 1.

Warranty

Refer to Ferco product warranty.

Options

- Row lettering type A
- Row lettering type E with Aisle light
- Round seat numbering
- Embroidery seat numbering / logo
- Flammability compliance with BS 5852 : 2006 Section 3 Ignition Source 5