



DIMENSIONS	
H	C
1100 (43.5")	700 (27.5")



PERTH STADIUM, AUSTRALIA

Product Specifications

Structure

- Combination of a wooden panel frame and a steel frame, covered with foam then, upholstered in leatherette / leather / fabric.

Backrest and Seat

- Motorized backrest with Inner panel made of 15mm thick press curved plywood, covered with foam of 50-120mm thickness and upholstered in fabric, density 45kg/m3.
- Rectangular shape, tapered front end.
- 15mm thick plywood upholstered with foam of 100-130mm thickness and covered with fabric.

Panel

- Fixed, shared armrest with cupholder in a smooth curve design.
- Decorative aisle panel made of steel structure and MDF board upholstered with padded covers.
- With cupholder on the front.

Recliner Mechanism

- Electrically motor operated.
- In compliance with EMC 2014/30/EU & LVD 2014/35/EU.
- Auto-return function.
- Push force (min. to max.): 2000N.
- Pull force (min to max.) : 2000N.
- Includes adapter (input) : 110V~240V (output) : DC 24V.
- Operating temperature : 0° - 40 °C.

Metal Finishing

- All metal parts exposed shall be stripped and cleaned with iron phosphate, hot water rinsed and then chromic acid rinsed.
- All metal parts are coated with an epoxy finish minimum of 60 microns for outdoor use.

Upholstery Finishing

- Refer Ferco standard fabrics / leatherettes / leather chart.

Fire Resistance

- Fire Safety - Flammability compliance with California Bulletin 117 and international regulations in their last issues and particularly with safety regulations.
- Flammability compliance with BS 5852 : 2006 Section 3 Ignition Source 0 & 1.

Warranty

- Refer to Ferco product warranty.

Options

- Dual USB charging port
- Auto return
- Embroidery logo
- Embroidery seat numbering
- Square light row lettering & numbering (80 x 80mm)
- Puck light
- Fixed backrest
- ¾ laminated outer back
- Headrest upholstered with leather
- Twin seat
- Flammability compliance with BS 5852 : 2006 Section 3 Ignition Source 5