



585 (23")  
610 (24")

H



C

DIMENSIONS	
H	C
Min. 940 (37")	Min. 815 (32")
Max 1000 (39.5")	Max 1000 (39.5")



FERCO SEATING ILLUSTRATION ONLY

**Product Specifications**

**Structure**

- Moulded structure holding the backrest and seat made up of 6 mm Thk. metal plate and 20mm x 20mm x 2mm rectangular hollow section with interchangeable backrest pitch.

**Backrest and Seat**

- Backrest (with Headrest) with inner structure made of Ø19mm x Thk 2.0mm metal frame covered with high resilience foam, upholstered in leatherette / leather / fabric. Topped with backrest and headrest paddings made from high resilience foam, upholstered in leatherette / leather / fabric.
- Seat unit with inner structure made of Ø19mm x Thk 2.0mm metal frame with high resilience foam upholstered in leatherette / leather / fabric and topped with Seat padding made from high resilience foam, upholstered in leatherette / leather / fabric.

**Armrests and Panel**

- Fixed with high resilience foam and black polyurethane for armrest and cupholder and cover with leatherette / leather / fabric.
- Wooden end panel upholstered in leatherette / leather / fabric.

**Legs**

- Legs are of lateral slope design made of a rectangular hollow section of 78mm x 38mm x 2.3mm Thk. continuously welded to 8mm thickness steel plate.

**Metal Finishing**

- All metal parts exposed shall be stripped and cleaned with iron phosphate, hot water rinsed and then chromic acid rinsed.
- All metal parts are coated with an epoxy finish minimum of 60 microns for outdoor use.

**Upholstery Finishing**

- Refer Ferco standard fabrics / leatherette / leather chart.

**Fire Resistance**

- Fire Safety - Flammability compliance with California Bulletin 117 and international regulations in their last issues and particularly with safety regulations.
- Flammability compliance with BS 5852 : 2006 Section 3 Ignition Source 0 & 1.

**Warranty**

- Refer to Ferco product warranty.

**Options**

- Embroidery logo
- Embroidery seat numbering
- Single seat / Linked seat
- Rocker backrest
- Foot cover
- Row lettering type A
- Row lettering type E with Aisle light
- Flammability compliance with BS 5852 : 2006 Section 3 Ignition Source 5