





20TH CENTURY FOX PRIVATE AUDITORIUM, MALAYSIA



535 (21.5") 560 (22")
585 (23") 610 (24")



DIMENSIONS		
P°	H	C
23°	1040 (41")	790 (31.5")
26°	1030 (40.5")	830 (33")

Product Specifications

Backrest

- Inner ply is made of 15 mm thick press curved plywood, covered with high resilience foam of 100-115mm thickness and upholstered in leatherette / leather / fabric.

Seat

- Seat unit with 15mm compressed plywood fully covered with high resilience foam of 125 - 160mm thickness and upholstered in leatherette / leather / fabric.

Armrests, Panel & Leg

- Made by high resilience foam and upholstered in leatherette / leather / fabric.
- Aisle panel made of MDF board and upholstered in leatherette / leather / fabric.
- Centre and end legs are made of a combination of two rectangular hollow section of 19mm x 38mm x Thk 2mm continuously welded to 6mm thickness steel plate.

Metal Finishing

- All metal parts exposed shall be stripped and cleaned with iron phosphate, hot water rinsed and then chromic acid rinsed.
- All metal parts are coated with an epoxy finish minimum of 60 microns for outdoor use.

Upholstery Material

- Refer Ferco standard fabrics/ leatherette / leather charts.

Fire Safety

- Fire Safety - Flammability compliance with California Bulletin 117 and international regulations in their last issues and particularly with safety regulations.
- Flammability compliance with BS 5852 : 2006 Section 3 Ignition Source 0 & 1.

Warranty

- Refer to Ferco product warranty.

Options

- Round seat numbering
- Row lettering type A
- Row lettering type E with Aisle light
- ¾ laminated outer back
- Embroidery logo
- Embroidery seat numbering
- Removable headrest cover
- Retractable intermediate armrest
- Tandem free standing/Tandem removable leg
- Castor wheel
- A.D.A Panel
- Tip-down seat
- Fixed seat
- Twin seat
- Rocker backrest
- Variable cupholders
- Flammability compliance with BS 5852 : 2006 Section 3 Ignition Source 5