


560 (22") 585 (23")
610 (24")



H

C

DIMENSIONS	
H	C
980 (38.5")	590 (23.5")



LA SALLE SCHOOL, SINGAPORE

Product Specifications

Backrest

- Trapezoidal shape, rounded headrest, with decorative stitching.
- Inner panel shall be made of 13 mm thick plywood upholstered with HR foam, density 45 kg/m³. Upholstered with padded cover.

Seat

- Rectangular shape, rounded front end, tip up.
- Inner panel made of Ø21mm tubular steel frame integrated in HR foams, density 60kg/m³.
- Upholstered with padded cover, removable by means of a zipper.
- Tip-up seat with counterweight mechanism allows the seat to return to vertical position by means of gravity. Totally silent and maintenance free.

Wrimatic

- Rubber wrimatic armrest.
- Heavy-duty die-cast aluminum alloy finished in oven baked epoxy powder coating to 60 micron.
- The arm consists of a complex swivel joint in precisely fabricated stainless steel with polish finish.
- Housed within the swivel joint is a maintenance-free bearing for long-term operation cycles.
- Static bearing load > 250 kgs – Dynamic bearing load > 40 kgs.
- Swivel plate supporting the writing board made of heavy-duty plate die-cast aluminum alloy in epoxy powder coating.
- The arm shall be clamped to the horizontal beam by means of a heavy-duty plate (die-cast aluminum alloy), with use of two Allen cap screws.
- Writing board made of 10 mm thick injection moulded ABS. Size: 300 by 425 mm.

Metal Finishing

- All metal parts exposed shall be stripped and cleaned with iron phosphate, hot water rinsed and then chromic acid rinsed.
- All metal parts are coated with an epoxy finish of at least 60 microns for indoor use.
- Conformity with BS-6496 hardness test.

Standards

- Rectangular hollow section of 76 x 38mm structural steel beam.
- Beam end protected with nylon capping.
- Fixed floor mounted.

Upholstery Material

- Refer to Ferco standard fabric / leatherette / leather charts.

Advantages

- Comfort especially studied according to fundamental criteria of ergonomic.
- Durability of the chair & after sales service for all spare parts of the model.
- Large choice of fabrics.

Fire Safety

- Fire Safety - Flammability compliance with California Bulletin 117 and international regulations in their last issues and particularly with safety regulations.
- Flammability compliance with BS 5852 : 2006 Section 3 Ignition Source 0 & 1.

Warranty

- Refer to Ferco product warranty.

Options

- Round seat numbering
- Plastic back outer (for only 585 & 610mm)
- Free standing leg / Removable leg
- Wooden back / seat outer
- Power point provision
- Row lettering Type E with Aisle light
- Row lettering Type A
- GPO socket provision
- Seat numbering on Wrimatic
- Beam round row lettering
- Castor wheel
- Diffuser leg
- Embroidery seat numbering / logo
- Removable leg
- Flammability compliance with BS 5852 : 2006 section 3 ignition source 5